

KAY JAY SERVICES

CONCRETE SEAL

Epoxy ester resin seals and protects

This heavy-duty concrete sealer is formulated with tough epoxy ester resins to offer concrete surfaces maximum resistance to oils, chemicals and abrasions. It quickly penetrates concrete and fills the pores to completely seal the surface, and dries to a clear, durable, chemical-resistant finish capable of withstanding heavy traffic. It can be used on new, or old concrete surfaces, and is traffic-ready in just 24 hours.

Use On:

- Floors
- Driveways
- Loading Docks
- Walls

Features and Benefits

- A tough, epoxy ester resin.
- Creates a durable, chemical-resistant finish.
- Penetrating seal fills the pores of concrete to eliminate dusting.

Properties

Appearance.....	Amber Liquid
Fragrance.....	Solvent odor
Concentrate.....	Yes
Specific gravity.....	0.857
VOC content.....	70-80%
Solubility.....	Insoluble in water

Directions Complete directions on product label

Allow new concrete to cure for a minimum of 90 days prior to sealing. Clean, rinse and dry the concrete. Then etch concrete using #140 Concrete Cleaner and Etch. When dry apply sealer using a lambs wool applicator. Apply at a rate of 300 - 500 sq. ft. per gallon.

Active Ingredients

Mineral spirits
Xylene
Epoxy Ester Resin
Ethyl Benzene
Methylethyl Ketoxime

CAS Number

8052-41-3
1330-20-7
Proprietary
100-41-4
96-29-7

Safety

Caution: Combustible. Harmful or fatal if swallowed. Keep away from heat or open flame. Keep out of the reach of children.

DOT Shipping (ground transportation)

Proper Shipping Name:	None
Class:	None
ID Number:	None
Package Group:	None

NFPA RATINGS

