

KAY JAY SERVICES

GYM FLOOR SEAL & FINISH

A polyurethane seal and high-gloss finish in one

Designed for use on soft or hardwood gym floors, this oil-modified polyurethane product is both a floor finish and a final seal. With a modern polyurethane resin, it provides a final seal and high-gloss finish that is both stain and chemical resistant. It contains 40 percent solids and dries quickly to provide a durable seal and finish capable of withstanding high traffic.

Use On:

- Wood Floors
- Hardwood Floors
- Softwood Floors

Features and Benefits

- Polyurethane resin dries to a clear, light-colored film with excellent durability.
- Provides a tough, glossy, stain and chemical-resistant finish to soft or hardwood gym floors.
- Withstands high traffic and offers superior protection against dirt and water.
- Self-leveling formula is easy to use.

Properties

Appearance.....	Amber Liquid
Fragrance.....	Solvent odor
Ready-to-use/Concentrate.	Both
Specific gravity.....	0.88
VOC Content.....	60.2% by wt.
Flash point.....	102°F
Stability.....	1 year
Application.....	Apply with lamb's wool applicator

Directions Complete directions on product label

To use as a sealer, dilute 3 parts product with 1 part mineral spirits.
For use as a finish, use undiluted.

For previously sealed floors, old sealer may be removed using a varnish remover, buffing and mineral spirits.

Seal new floor, sanded floor or prepared old floor using a clean lamb's wool applicator. Up to 3 coats may be required to properly seal the floor. After sealing, additional coats of undiluted finish are applied to provide a shiny, resistant finish.

Active Ingredients

Active Ingredients	CAS Number
Petroleum Distillate	64742-88-7
Urethane Modified Soya Alkyd Resin	Proprietary
Mineral Spirits	8052-41-3
Medium Oil Alkyd Resin	Proprietary
Trimethyl Benzene.....	25551-13-7

Safety

Caution: Combustible material. Harmful or fatal if swallowed.

DOT Shipping (ground transportation)

Proper Shipping Name:	None
Class:	None
ID Number:	None
Packing Group:	None

NFPA RATINGS

