KAY JAY SERVICES

ASPHALT PATCH

Paving Patch Material

Cracks, potholes and fault lines are the pits to fill. With "Asphalt Patch" you have an easy, durable solution for filling those annoying, unattractive craters in the pavement. This hardy sealant is made from a mix of flexible yet resilient ingredients including screened aggregate, tar and asphalt binders. It remains pliable within its container until it is applied to pavement surfaces. Even when temperatures dip as low as 15°F, it remains loose enough for easy application. Once applied, cracks remain sealed, even in the most severe weather.

Use For Repairing:

Brick roads

- Asphalt
- Black Top
- Parking areas
- Driveways
- Playgrounds

Features and Benefits

- · Can be used in any weather
- No primer Coat is needed
- Can be used in temperatures as low as 15°F

Properties

Appearance Black liquid
Fragrance Petroleum odor

 Ready to Use......
 Yes

 Specific gravity.....
 1.01

 Flash point......
 450° F

Stability...... 2 years at 70° F

Directions Complete directions on product label Brush way dust and dirt then simply fill crack or hole.

Active Ingredients

CAS Number

 Asphalt
 8052-42-4

 Hydrogen Sulfide
 7783-06-4

Safety

Caution: Avoid breathing vapors. Keep out of the reach of children

DOT Shipping (ground transportation)

 Proper Shipping Name:
 None

 Class:
 None

 ID Number:
 None

 Package Group:
 None

NFPA RATINGS

Flammability

