

KAY JAY SERVICES

CONCRETE PATCH

Concrete Patch is a Portland cement based formula that is specially formulated for making structural repairs to vertical and overhead surfaces. It can be used anywhere that rapid setting is necessary.. Its unique properties allow the user to actually sculpt the material as it begins to harden. Quick-Setting

Use on:

- Driveways
- Concrete Pipes
- Pre-Stress Panels
- Concrete Highways
- Sewers And Culverts
- Loading Docks
- Roads And Pavement
- Curbs
- Retaining Walls
- Bridge Decks
- Cold Storage Vaults
- Septic Tanks

Features and Benefits

- Combines the compressive strength of concrete with the impact resistance of glass fibers.
- Rapid hardening formula will help reduce traffic build-up.
- Withstands the contraction and expansion of freeze/thaw cycles.
- Sets in approximately 10 minutes

Properties

Form.....	Powder
Color.....	Gray
Odor.....	None
Solubility.....	Slight
Flash Point.....	None
Density.....	2.6-3.2 ± 0.05 lbs/ga
Storage Stability.....	Stable

Directions

Complete directions on product label

Mix product with water for 3-4 minutes. Apply mixture within 10-20 minutes of mixing. This time will be influenced by weather conditions. To lengthen set times during hot weather – use ice-cooled water for batching – keep in shade – keep equipment cool by washing with cold water. No curing membranes are required. Traffic must be kept off the patch for one (1) hour.

Active Ingredients

Active Ingredients	CAS Number
Silica, Sand Crystalline.....	14808-60-7
Portland Cement.....	65997-15-1
Gypsum.....	10101-41-4
Lime.....	1305-62-0

Safety

Warning - Do not breath dust. Can cause irritation to eyes and lungs. May cause dryness or burns to skin. Keep out of the reach of children

DOT Shipping (ground transportation)

Proper Shipping Name:	None
Class:	None
ID Number:	None
Package Group:	None

NFPA RATINGS



