LED Canless Regressed Downlight

Interchangeable Trims

LED recessed lighting is a versatile and convenient lighting option for any space, whether you are doing a home remodel or working with new construction. This canless downlight is designed to be an all-in-one solution that is quick, easy to install, and offers customizable color options. With five color options, 27K/30K/35K/40K/50K. Each recessed ceiling light has a junction box with quick connectors for simple wiring. The included interchangeable trim features a twist lock application that is easy to change the trim style in the future. In addition, with the ability to dim from 100% to 10%, you can control the light output according to your mood and preferences. Moreover, the wet location rating makes the LED recessed lighting suitable for outdoor and bathroom environments where moisture may be present. The LED recessed lighting is built to last, with an astounding 50,000hour lifetime.





















COB LED Color Selectable 27K/30K/35K/40K/50K




Twist lock application that is easy to change the trim style



2" | 15W | 1055lms



4" | 18W | 1360lms



Regressed Trims



6" | 24W | 1735lms







Mounting	Option
87705-SU	Construction Plate

Trim for 8	5589-SU	Trim			
85592-SU	TRIM/DAD/2R/BK	2" Black Round			
85593-SU	TRIM/DAD/2R/BN	2" Brushed Nickel Round			
85594-SU	TRIM/DAD/2S/WH	2" White Square			
85595-SU	TRIM/DAD/2S/BK	2" Black Square			
85596-SU	TRIM/DAD/2S/BN	2" Brushed Nickel Square			

Trim for 85	590-SU	Trim			
85597-SU	TRIM/DAD/4R/BK	4" Black Round			
85598-SU	TRIM/DAD/4R/BN	4" Brushed Nickel Round			
85599-SU	TRIM/DAD/4S/WH	4" White Square			
85600-SU	TRIM/DAD/4S/BK	4" Black Square			
85601-SU	TRIM/DAD/4S/BN	4" Brushed Nickel Square			

Trim for 85	5591-SU	Trim			
85602-SU	TRIM/DAD/6R/BK	6" Black Round			
85603-SU	TRIM/DAD/6R/BN	6" Brushed Nickel Round			
85604-SU	TRIM/DAD/6S/WH	6" White Square			
85605-SU	TRIM/DAD/6S/BK	6" Black Square			
85606-SU	TRIM/DAD/6S/BN	6" Brushed Nickel Square			

	Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
2"	85589-SU	LFX/DAD/2R/15W/90CRI/5SCT/WH	15	1055	120	27K/30K/35K/40K/50K	50000	WL,DIM,ES	(H) 4.92 (D) 3.13
4"	85590-SU	LFX/DAD/4R/18W/90CRI/5SCT/WH	18	1360	120	27K/30K/35K/40K/50K	50000	WL,DIM,ES	(H) 4.8 (D) 4.5
6"	85591-SU	LFX/DAD/6R/24W/90CRI/5SCT/WH	24	1735	120	27K/30K/35K/40K/50K	50000	WL,DIM,ES	(H) 2.95 (D) 7.3
DIM = Dimmable WL = Rated Wet Location ES = Energy Star									